



ASSEMBLAGE					
ITEM	REQ'D	NAME	FIGURE	PLAN	
1	1	FRONT AND LOCK ROD.	30622	5-306	
2	1	OPERATING ROD.	3333	5-333	
3	2	TIE STRAPS.	3002	5-300	
4	1	BASE PLATE.			
5	1	MOVEMENT COMPLETE WITH CIRCUIT CONTROLLER.			
6	1	COVER COMPLETE.			
7	1	SWITCH MECHANISM COMPLETE WITH 4, 5, & 6.			
8	8	WASHERS.	2161	5-216	
	</				

NOTE:-  
 SWITCH RODS, GAUGE PLATE AND  
 RAIL BRACES TO BE FURNISHED WITH  
 SWITCH POINTS; FOR DETAILS SEE  
 STANDARD M.W. MATERIAL PLANS.  
 WHERE NO DETAIL REFERENCE  
 IS GIVEN, THE MANUFACTURER'S  
 STANDARD APPARATUS SHOULD BE  
 FURNISHED.  
 FOR FRAMING OF TIMBERS  
 SEE PLAN 5-210.

# REVISIONS

1 SHEET

S-212-A



THE PENNSYLVANIA RAILROAD  
 STANDARD  
 LAYOUT

SLIP SWITCH - "AI" MECHANISM WITHOUT CYLINDER

OFFICE OF CHIEF SIGNAL ENGINEER, PHILA., PA. NOV. 22, 1927

Approved

*A. H. R.*  
 Chief Signal Engineer

Approved

*J. H. M.*  
 Chief Engineer

11/10/27  
 11/10/27  
 11/10/27