

[illegible]

NOTES:-

1. WHERE ASPECT NO. 5 IS USED ON SIGNAL 4001, LOCATED BETWEEN TRACKS, THE TRACKS SHALL BE NOT LESS THAN 19'-0" CENTERS.
2. CIRCULAR BACKGROUND SHALL BE FURNISHED FOR TOP ARM OF ALL SIGNALS, EXCEPT AS PROVIDED IN NOTE 5.
3. BACKGROUND 4012 SHALL BE FURNISHED FOR BOTTOM ARM, ONLY WHERE ASPECT NO. 6 OR NO. 8 IS TO BE DISPLAYED.
4. ALL OPENINGS IN BACKGROUND SHALL BE CUT; THOSE NOT USED SHALL BE COVERED WITH SHEET IRON DISCS.
5. USE 4002 WHERE PRACTICABLE, WITHOUT BACKGROUND, FOR TAKE SIDING INDICATOR—ASPECT NO. 12.
6. SIGNALS SHALL BE COMPLETE WITH HUB, NECESSARY RADIAL PIPING, JUNCTION BOX, BACKGROUND, LAMP UNITS AS ORDERED, BOLTS, ETC., FOR INSTALLATION, EXCEPT FOUNDATION BOLTS AND STEEL CHANNELS.
7. FOR BRIDGES SPANNING MORE THAN 6 TRACKS, CROSS SECTION OF BRIDGE SHOULD ACCOMPANY ORDER.
8. FOR ARRANGEMENT OF TERMINALS SEE STANDARD PLAN S-858.
9. WHEN ORDERING SIGNALS SPECIFY FIGURE NUMBER, TOGETHER WITH ASPECTS DESIRED.
10. WHERE NO DETAIL REFERENCE IS SHOWN, THE MANUFACTURER'S STANDARD APPARATUS SHALL BE FURNISHED.
11. DRILL MAST FOR WIRES, ONLY AS REQUIRED FOR ASPECTS ORDERED.
12. WHERE DEPTH OF BRIDGE CHORD IS OTHER THAN THAT SHOWN ON 4004 OR 4005, THE ACTUAL DEPTH SHOULD BE SPECIFIED ON ORDER.

REVISIONS
REDRAWN FROM APPROVED PLAN S-400-D, DATED 2-17-27 AND REVISED.