

LAMP SUPPORT
SOCKET TYPE 127

TARGET M-32
Specify color by symbol
White & Yellow M-32-WY
White & Red M-32-WR
Yellow & Red M-32-YR

MAST 179

THROW LEVER 90

SEGMENT GEAR 1607

TOP EXTENSION 195

TOP 6-A

SPINDLE 63

LAMP SUPPORT
PLUG TYPE 129

TOP 2-A


BOTTOM 43

CRANK 67


LOW 50-A

INTERMEDIATE 50-B

CROSS PIN 61 COTTER RING 1611




LATCH 465
(Malleable Iron)



LATCH 1297
(Forged Steel)

Either type may be furnished



OPERATING ROD
7'-0" - 1609 10'-0" - 1610

ROD SUPPORT 1608

NOTE:-

Operating Rod, Rod Support and two Latches are furnished with each Switch Stand.

Requisitions must specify the name and number (as designated) of the material required, and the number of the plan.

In addition to the above, requisitions for Low 50-A must specify length of Rod required, and requisitions for Intermediate 50-B must specify color of Target by symbol.

73900-A



PENNSYLVANIA RAILROAD SYSTEM
STANDARD

NEW CENTURY SWITCH STAND
LOW AND INTERMEDIATE MODELS

OFFICE OF CHIEF ENGINEER, PHILA., PA., JUNE, 1923.

Correct
W. E. Lushington
Engineer of Standards

Approved
[Signature]
Chief Engineer