



Letters for Signs shall be in accordance with Standard Plan of Letters and Numerals, 78011-(). The height of letter desired shall be achieved by the proportional or visual aid method of enlargement. Spacing between letters shall be well balanced to attain a symmetrical appearance. Spacing between parts of names or words shall generally be $\frac{3}{4}$ of the height of the letters.

Passenger Station Signs shall use the extended (full size) type of letters, except where length of name and end spacing exceeds the area (space) in which the sign will be placed.

Passenger Station Signs shall be two in number, shall be located on each end of Passenger Station or Passenger Station Platform Shelter.

The face of sign shall be covered with Special 650 Series Green, Color Standard RQ15634 Scotchcal Brand Marking Film with No. 2270 Wide Angle Silver Flat-Top Scotchlite letters.

Aluminum for Signs shall be thoroughly cleaned and degreased by a suitable method before applying sheeting material.

Signs shall be attached by $\frac{5}{16}$ " Dia. x $3 \frac{1}{2}$ " Lg. Aluminum Lag Screws or by Aluminum Bolts of suitable length.

Aluminum Signs shall have a back support of 1" Wood or Marine Plywood shaped to conform with the dimensions of the Sign.



78166-A

PASSENGER STATION SIGN

APRIL 1970

[Signature]
Chief Engineer - Maintenance of Way

[Signature]
Ass't. Vice President - Engineering